OP-600L OPTY™

The OPTY™ OP-600L glove is our new glove protective against chemical risks in dry, oily or humid environments. Thanks to the rough finish on the palm, the adhesion is excellent in every environment. The triple PVC coating ensures a perfect oil resistance. The liner made of seamless cotton offers an incomparable dexterity. The hands of the users are fully protected thanks to the length (30cm).

EN 374-1: AJK / A = Methanol / J = n-Heptane / K = Sodium Hydroxide 40%

PRODUCT INFORMATION

PROTECTION	Liquids, chemicals and industrial oils
MATERIAL	**Coating:** PVC, triple dip, long cuff **Liner:** 13 gauge/cotton, white
COLOUR	Blue
PACKAGING	12 pairs/polybag; 72 pairs/box
SIZES	8/M, 9/L, 10/XL

COMPLIANCY

EN 388 — 4121X
EN 374-1 — AJK
EN 374-5

REACH COMPLIANT

CONFIDENCE IN TEXTILES
Tested for harmful substances according to Oeko-Tex® Standard 100 Institute

CERTIFICATION	EN388:2016; ISO 374-1:2016 Type B; EN ISO 374-5:2016
PROTECTION RATING	ACTPS1: 4121X and AJK rating

EVALUATION (RATING 1 TO 10)

Dry grip	1 2 3 4 5 6
Wet grip	1 2 3 4 5 6 7 8
Oil grip	1 2 3 4 5 6 7 8
Dexterity	1 2 3 4 5 6 7 8
Breathability	1 2 3 4
Comfort	1 2

ENVIRONMENTS

Maintenance in wet environment (water, grease, oils, hydrocarbons), chemical handling, treatment of metals, petrochemical, automotive industry, general maintenance and handling works.

RECOMMENDATION

WATER & LIQUID RESISTANCE: Suitable for handling in wet conditions.
CHEMICAL RESISTANCE: Offers protection against chemicals EN 374-1: AJK.
GAUNTLET STYLE: Suitable for extremely wet conditions.

DIMENSIONS *(Tolerance ± 5%)*

SIZE	6/XS	7/S	8/M	9/L	10/XL	11/XXL
Overall length (mm)			305	310	313	315
Palm width (mm)			100	103	110	112
Length of middle finger (mm)			80	80	85	90
Thickness (µm)			1500	1500	1500	1500
Weight (g/pair)			128	128	135	140
Liner weight (g/pair)			60	60	64	68
Coating weight (g/pair)			68	68	71	72

OP-600L OPTY™

EN388:2016 | EN 374-1 | EN 374-5 ACTPS1: 4121X AND AJK

	PERFORMANCE LEVEL								
	TEST		0	1	2	3	4	5	X
A	Abrasion Resistance	Cycles	< 100	100	500	2000	8000		
C	Coup Cut *	Newtons	< 1.2	1.2	2.5	5.0	10.0	20.0	
		Gram Conv	< 119g	120g-249g	250g-499g	500g-999g	1000g-1999g	> 2000g	
T	Tear Resistance	Newtons	< 10	10	25	50	75		
P	Puncture	Newtons	< 20	20	60	100	150		

			A	B	C	D	E	F	X
S	ISO Cut**	Newtons	2	5	10	15	22	30	
		Gram Conv	204	509	1020	1530	2243	3059	

		P	F	X
I	Impact TEST			

* Weight needed to cut with 1" (25mm) blade travel
** A Cut 5 Glove with 2000g force is approximately Level D for ISO cut
X = not tested or not applicable

For details of your nearest **REBEL** distributors contact us:
Tel: 011 663 2700 | Email: info@rebelsafetygear.com
www.rebelsafetygear.com

1FEBRUARY2020