



PRODUCT CODE: HS-HZNLLN-20M **PRODUCT DESCRIPTION:** 20 Metre Temporary Horizontal Lifeline

PRODUCT COMPLIANCE

CERTIFICATION	EN795 Class C – Flexible anchor points EN795 Class B – Anchor sling EN362 – Connector
PACKAGING	Individually packed in a box and serial numbered with user instruction leaflet.

MATERIALS

WEBBING	<ul style="list-style-type: none"> • 30mm wide polyester webbing (lifeline) • 44mm wide polyester webbing (anchor point)
D-RINGS	<ul style="list-style-type: none"> • 50mm wide D-Ring (anchor point)
RATCHET	Corrosion-resistant steel ratchet

TECHNICAL FEATURES

LIFELINE WEBBING	20m bright yellow webbing with a loop on each end to connect with to a carabiner.
ANCHOR STRAP (2)	Versatile straps used to setup lifeline between 2 anchor points .
CARABINER (2)	Screw gate carabiner with automatic closing function which connects the Temporary Lifeline to an anchor point.
CARRY BAG	Designed to store all components of this system and protect it from possible damage.
RATCHET SYSTEM	The simple ratchet system is easy to use whilst effective at creating a tensioned lifeline.

SUGGESTED ENVIRONMENTS

This product has been designed to be used in a covered environment which is not exposed to the outdoor elements for extended periods of time.

WARNINGS

MAXIMUM WEIGHT	Certified to a maximum of 2 x 140kg users – 280kg.
CONNECTIONS	This device must be securely set up between certified anchor points as well as connected by a certified connector.
POSITIONING	This device must be setup as high as possible to reduce the fall clearance as well as trip hazard.
PRODUCT LIFESPAN	The components have a maximum lifespan of 5 years.
IN THE EVENT OF A FALL	Should this product have been subject to a fall, or there is visible damage, it should be removed from service immediately and not used until it has been inspected by a REBEL Subject Matter Expert.
INTERMEDIATES	Should this product span a length of more than 5 metres there must be an intermediate included in the system to reduce the forces in the event of a fall as well as fall clearance.
EXPOSURE	This product is designed for temporary use – It should not be left setup for periods longer than 5 days at any given time.
COMPLY TO INSTRUCTION MANUAL	The user must comply to the user instruction manual. Not adhering could lead to serious injury or death.